



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

---

**Section 1 • Product and Company Identification**

---

**Product Name:** LPS® Micro-X

**Part Number(s):** 04516 (aerosol), 04555, C04516 (aerosol), C04555

**Chemical Name:** Hydrocarbon / Isopropanol Mixture

**Product Use:** A fast drying industrial cleaning solvent designed to remove soil and other contaminants.

**Manufacturer Information:** LPS Laboratories, 4647 Hugh Howell Road, Tucker, GA, USA 30084  
**TEL:** USA & Canada: 1 800 241-8334  
Outside USA and Canada: +1 770 243-8800  
**FAX:** USA & Canada: 1 800 543-1563  
Outside USA and Canada: +1 770 243-8899

**Emergency Telephone Number:** Chemtrec: USA & Canada: 1 800 424-9300  
Outside USA and Canada: +1 703 527-3887

**Website:** <http://www.lpslabs.com>

---

**Section 2 • Hazards Identification**

---

*This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

**Emergency Overview:**

**Aerosol:** DANGER: Extremely flammable. Contents under pressure. Harmful or fatal if swallowed.

**Bulk:** DANGER: Extremely flammable. Harmful or fatal if swallowed.

**Primary route(s) of entry:** Skin and eye contact. Inhalation.

**Potential Acute Health Effects:**

**Eyes:** Irritating to eyes.

**Skin:** Repeated exposure may cause skin dryness or cracking.

**Inhalation:** Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

**Ingestion:** Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

**Potential Chronic Health Effects:**

**Carcinogenic Effects:** NTP: No IARC: No OSHA: No ACGIH: No

**Mutagenic Effects:** None

**Teratogenic Effects:** This material (or component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

**Target Organs:** Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation. Prolonged and repeated inhalation of high levels of mixed isomers of hexane resulted in kidney damage in male rats. The effects observed are the same as those seen in male rats exposed to other hydrocarbons. The mechanism by which these chemicals cause the characteristic kidney toxicity is unique to the male rat and the kidney effects are not expected to occur in man. Breathing isopropanol vapors has caused damage to the lining of the middle ear in experimental animals. The relevance of this finding to humans is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: liver abnormalities, kidney damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: central nervous system effects.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

**Medical conditions aggravated by exposure:**

Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

**Signs and Symptoms**

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

---

**Section 3 • Composition / Information on Ingredients**

---

Component	CASRN	Weight Percent
2-Methylpentane	107-83-5	40 - 50%
3-Methylpentane	96-14-0	10 - 20%
2,3-Dimethylbutane	79-29-8	10 - 20%
2,2-Dimethylbutane	75-83-2	5 - 10%
n-Heptane	142-82-5	1 - 5%
Isopropanol	67-63-0	1 - 5%
Carbon Dioxide (aerosol only)	124-38-9	1 - 5%
n-Hexane	110-54-3	1 - 3%

---

**Section 4 • First Aid Measures**

---

<b>Eyes:</b>	Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. DO NOT use eye ointment. Seek medical attention immediately.
<b>Skin:</b>	Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. DO NOT use ointments. Seek medical attention if irritation persists.
<b>Inhalation:</b>	Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. DO NOT leave victim unattended. Seek medical attention immediately.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

---

**Section 5 • Fire Fighting Measures**

---

**Products of Combustion:** Carbon monoxide and carbon dioxide.

**General Fire Hazards:** Do not use on energized equipment. High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers.

**Firefighting media:** SMALL FIRE: Use DRY chemical powder.  
LARGE FIRE: Use CO<sub>2</sub>, water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, auto-ignition or explosions.

**Sensitivity to Impact:** None                      **Sensitivity to Static Discharge:** Yes

**Protection Clothing (Fire):** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

**Special Remarks on Explosion Hazards:**  
Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

---

**Section 6 • Accidental Release Measures**

---

**Containment Procedures:**

**Small Spill and Leak:** Eliminate ignition sources. Absorb with an inert material and dispose of properly.

**Large Spill and Leak:** Eliminate ignition sources. Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.

**Clean-Up Procedures:** Recover free product and place in a suitable container for disposal.

**Evacuation Procedures:** Ventilate area of leak or spill. Keep unnecessary and unprotected people away.

**Special Procedures:** Remove all sources of ignition. Ventilate area. Wear personal protective equipment during cleanup.

---

**Section 7 • Handling and Storage**

---

**Handling:** DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists.

**Storage:** Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F (49°C).

**Precautions to be taken in handling and storage:**  
Store aerosols as Level 3 Aerosol (NFPA 30B). Store bulk liquids as NFPA Class 1B liquid. Store all materials in a dry, well-ventilated area. Avoid breathing vapors. Ground and bond containers before transferring materials.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

**Section 8 • Exposure Controls / Personal Protection**

**Exposure Guidelines:**

Component	CASRN	OSHA	ACGIH	NIOSH	Supplier
2-Methylpentane	107-83-5	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
3-Methylpentane	96-14-0	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
2,3-Dimethylbutane	79-29-8	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
2,2-Dimethylbutane	75-83-2	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
n-Heptane	142-82-5	500 ppm PEL	400 ppm TLV 500 ppm STEL	85 ppm TWA	500 ppm STEL
Isopropanol	67-63-0	400 ppm PEL	200 ppm TLV 400 ppm STEL	400 ppm TWA 500 ppm STEL	400 ppm TWA
Carbon Dioxide (aerosol only)	124-38-9	5000 ppm PEL	5000 ppm TLV 30000 ppm STEL	5000 ppm TWA 30000 ppm STEL	None reported

**Engineering Controls:** Provide general and/or local exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

**Personal protective equipment**

**Eye protection:** Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

**Hand protection:** Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, wear chemical resistant gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves. Take into consideration the specific local conditions under which the product is used, such as the danger of the cuts, abrasion and the contact time.

**Respiratory protection:** Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e. organic vapor cartridge).

**General Hygiene Considerations:** Wash thoroughly after handling. Have eye-wash facilities immediately available.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

---

**Section 9 • Physical and Chemical Properties**

---

<b>Appearance:</b>	Clear liquid	<b>Color:</b>	Colorless / water-white
<b>Odor:</b>	Mild or faint alcohol	<b>Evaporation Rate:</b>	< 1 (Ethyl Ether = 1)
<b>Solubility Description:</b>	< 5% by weight	<b>Flash Point:</b>	-18°C (0°F) - dispensed liquid
<b>Boiling Point:</b>	60.5°C (141°F) - dispensed liquid	<b>Flash Point Method:</b>	Tag-Closed Cup
<b>Specific Gravity (H<sub>2</sub>O=1):</b>	0.65 - 0.68 @ 20°C	<b>Decomposition Temperature:</b>	Not established
<b>Vapor Density (air = 1):</b>	~3	<b>Auto ignition temperature:</b>	306°C (583°F)
<b>Vapor Pressure:</b>	352 mm Hg @ 38°C	<b>Flammable limits (estimated):</b>	LOWER: 1.2% UPPER: 7.0%
<b>Rule 1171 PPc:</b>	Not established	<b>Partition Coefficient (octanol/water):</b>	< 1
<b>V.O.C. Content:</b>	Aerosol: 95.8% per State & Federal Consumer Product Regulations; 630 g/L per SCAQMD Rule 102 Bulk: 100% per State & Federal Consumer Product Regulations; 657 g/L per SCAQMD Rule 102	<b>Odor Threshold:</b>	Not established
<b>Melting Point:</b>	Not established	<b>Viscosity:</b>	< 3 cSt @ 25°C
<b>pH:</b>	Not applicable	<b>Volatiles:</b>	100%
<b>Heat of combustion:</b>	Aerosol: > 30 kJ/g Bulk: > 30 kJ/g		

---

**Section 10 • Stability and Reactivity**

---

<b>Chemical Stability:</b>	Product is stable under recommended storage conditions.
<b>Conditions to Avoid:</b>	Keep away from heat and ignition sources. Avoid exposure to direct sunlight for extended periods and temperatures in excess of 122°F (50°C).
<b>Incompatibility:</b>	Extremely reactive or incompatible with oxidizing agents.
<b>Hazardous Decomposition:</b>	Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include carbon monoxide and carbon dioxide.
<b>Hazardous Polymerization:</b>	Will not occur.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

**Section 11 • Toxicological Information**

**Acute and Chronic Toxicity**

**A: General Product Information**

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

**B: Component Analysis**

Component	CASRN	LC-50	LD-50
2-Methylpentane	107-83-5	> 3125 ppm / rat / 4 hr*	Not established
3-Methylpentane	96-14-0	Not established	Not established
2,3-Dimethylbutane	79-29-8	Not established	Not established
2,2-Dimethylbutane	75-83-2	Not established	Not established
n-Heptane	142-82-5	103 g/m3 / rat / 4 hr	222 mg/kg / intravenous / mouse
Isopropanol	67-63-0	16000 ppm / rat / 4 hr*	5045 mg/kg / oral / rat* 5030 - 7900 mg/kg / dermal / rabbit*
Carbon Dioxide (aerosol only)	124-38-9	Not established	Not appropriate
n-Hexane	110-54-3	48000 ppm / rat / 4 hr*	25 g/kg / oral / rat* 1.3 g/kg / dermal / rabbit*

\* Supplier Data

**Section 12 • Ecological Information**

**Mobility:** Volatile. Readily absorbed into soil. **Persistence / Degradability:** Only slightly biodegradable

**Bioaccumulative potential:** Minimal bioaccumulation potential **Other adverse effects:** None known

Ecological studies have not been conducted for this product. The following information is available for component(s) of this product.

**Ecotoxicity**

Effects on Organisms	Component	CASRN	Test	Species	Results
<b>Acute Toxicity on Fishes</b>	Isopropanol	67-63-0	24-hr LC50	Carassius Auratus	5,000,000 µg/L
	n-Hexane	110-54-3	48-hr LC100	Leuciscus Idus Melanotus	260,000 µg/L
<b>Acute Toxicity on Daphnia</b>	2-Methylpentane	107-83-5	48-hr EC50	Daphnia Magna	2.1 mg/L
	Isopropanol	67-63-0	24-hr LC50	Daphnia Magna	10,000,000 µg/L
	n-Hexane	110-54-3	24-hr LC50	Daphnia Magna	50,000 µg/L
<b>Bacterial Inhibition</b>	No data available				
<b>Growth inhibition of algae</b>	Isopropanol	67-63-0	48-hr EC50	Scenedesmus Quadricauda	1,800,000 µg/L
	n-Hexane	110-54-3	EC50	Anabaena Inaequalis	1.7%
<b>Bioaccumulation in fish</b>	No data available				

\* Supplier Data



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

**Section 13 • Disposal Considerations**

**Waste Status:** Aerosol cans, if depressurized and emptied to less than 1 inch (2.54 cm) of fluid contents, are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, the aerosol carries the waste codes D001 and D003 (U.S.). Dispensed product, as received, carries the waste codes D001 and D003 (U.S.).

**Disposal:** Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

**Note:** Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

**Section 14 • Transport Information**

Aerosol

D.O.T. Ground	Shipping Name:	ORM-D	UN No.:	NA
	Hazard Class:	NA	Technical Name:	NA
	Subclass:	NA	Hazard Label:	ORM-D Already on box
	Packing Group:	NA		
Road/Rail - ADR/RID	UN No.:	1950	ADR Class:	2.1
	Packing Group:	NA	Classification Code:	5F
	Name and description:	AEROSOLS, flammable	Hazard ID No.:	NA
	Labeling:	2.1	Technical Name:	NA
IMDG-IMO	UN No.:	1950	Class:	2.1
	Shipping Name:	Aerosols	Subsidiary Risk:	NA
	Labeling:	2	Packing Group:	NA
	Packing Instructions:	P003, LP02	EmS:	F-D, S-U
IATA - ICAO:	UN No.:	1950	Class:	2.1
	Shipping Name:	Aerosols, flammable	Subclass:	NA
	Packing Instructions:	203, Y203 (Ltd. Qty.)	Packing Group:	NA
	Labeling:	Flammable Gas	Technical Name:	NA

Bulk

D.O.T. Ground	Shipping Name:	Flammable Liquid, n.o.s.	UN No.:	1993
	Hazard Class:	3	Technical Name:	Hexanes, Isopropanol
	Subclass:	NA	Hazard Label:	Flammable Liquid
	Packing Group:	NA		
Road/Rail - ADR/RID	UN No.:	1993	ADR Class:	3
	Packing Group:	II	Classification Code:	F1
	Name and description:	Flammable liquid, n.o.s.	Hazard ID No.:	33
	Labeling:	3	Technical Name:	Hexanes, Isopropanol
IMDG-IMO	UN No.:	1993	Class:	3
	Shipping Name:	Flammable liquid, n.o.s.	Subsidiary Risk:	NA
	Labeling:	3	Packing Group:	II
	Packing Instructions:	P001	EmS:	F-E, S-E
IATA - ICAO:	UN No.:	1993	Class:	3
	Shipping Name:	Flammable liquid, n.o.s.	Subclass:	NA
	Packing Instructions:	Y341 (Ltd. Qty.), 353, 364 (CAO)	Packing Group:	II
	Labeling:	Flammable Liquid	Technical Name:	Hexanes, Isopropanol

\*Note: For air shipment only  
5 gallon (18.93 liter) containers must be shipped via "CARGO AIRCRAFT ONLY" (CAO).  
55 gallon (208 liter) drums CANNOT be shipped by air.

The preceding information is subject to change and must be verified prior to shipment. It is the responsibility of anyone offering hazardous materials for shipment to ensure compliance with all applicable regulations.



MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

**Section 15 • Regulatory Information**

**U.S. Federal Regulations**

**RCRA Hazardous Waste No.:** D001, D003 (aerosols only)

**Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA):**  
n-Hexane 110-54-3 5000 lbs

**Toxic Substances Control Act (TSCA):**  
All components of this product are TSCA inventory listed and/or are exempt.

**Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories:**  
Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

**This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):**  
n-Hexane 110-54-3 3% max.

**Section 112 Hazardous Air Pollutants (HAPs):** n-Hexane

**State Regulations**

**California:** This product contains chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm.

**California and OTC States:**  
Aerosol: This product does not conform to consumer product regulations.  
Bulk: Not for sale in California. In other jurisdictions, this product is not regulated by consumer product regulations.

**New Jersey Right to Know:**  
Aerosol: 2-Methylpentane 107-83-5 • 3-Methylpentane 96-14-0 • 2,3-Dimethylbutane 79-29-8 • 2,2-Dimethylbutane 75-83-2 • n-Heptane 142-82-5 • Isopropanol 67-63-0 • n-Hexane 110-54-3 • Carbon Dioxide 124-38-9  
Bulk: 2-Methylpentane 107-83-5 • 3-Methylpentane 96-14-0 • 2,3-Dimethylbutane 79-29-8 • 2,2-Dimethylbutane 75-83-2 • n-Heptane 142-82-5 • Isopropanol 67-63-0 • n-Hexane 110-54-3

**International Regulations**

**Canadian Environmental Protection Act (CEPA):**  
All of the components of this product are included on the Canadian Domestic Substances list (DSL).

**Canadian Workplace Hazardous Materials Information System WHMIS:**  
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**WHMIS Classification:**  
Aerosol: Class A, Class B5, Class D2B

**WHMIS Classification:**  
Bulk: Class B2, Class D2B

**Other Regulations:**  
Montreal Protocol listed ingredients: None  
Stockholm Convention listed ingredients: None  
Rotterdam Convention listed ingredients: None  
RoHS Compliant: Yes






MATERIAL SAFETY DATA SHEET  
LPS® Micro-X

Revision Date: August 24, 2011

Supersedes: July 10, 2009

Section 16 • Other Information

MSDS#: 14516 MSDS Preparation Responsible Name: Elena Badiuzzi Compliance Manager Telephone: +1 770 243-8800	HMIS 1996		HMIS III		Health  Reactivity Special
	Health:	2	Health:	[*] 2	
	Flammability:	3	Flammability Aerosol:	4	
			Flammability Bulk:	3	
	Reactivity:	0	Physical Hazard Aerosol:	2	
			Physical Hazard Bulk:	0	

**Notice to Reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Elena Badiuzzi, Compliance Manager  
LPS Laboratories, a division of Illinois Tool Works