# **Material Safety Data Sheet**





Revision Number: 002.1 Issue date: 03/18/2009

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 554 Thread Sealant Refrigerant IDH number: 231643

Sealant

Product type: Anaerobic Sealant Item number: 25882

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

1001 Trout Brook Crossing Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

<u>HMI</u>S:

Physical state:LiquidHEALTH:\*2Color:RedFLAMMABILITY:1Odor:CharacteristicPHYSICAL HAZARD:1

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:May cause respiratory tract irritation.Skin contact:May cause allergic skin reaction.

**Eye contact:** Mild eye irritation.

**Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Bisphenol A fumarate resin	39382-25-7	30 - 60
Cumene hydroperoxide	80-15-9	1 - 5

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

**Skin contact:** Wash with soap and water. Remove contaminated clothing and footwear.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: If product is involved in fire extinguish with dry powder, foam or carbon

dioxide.

**Special firefighting procedures:** Wear self contained breathing apparatus.

Unusual fire or explosion hazards: Not available

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Ventilate area.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

# 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

**Storage:** For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Bisphenol A fumarate resin	None	None	None	None
Cumene hydroperoxide	None	1 ppm (6 mg/m3) None TWA None (SKIN)		None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

imits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:**Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:RedOdor:CharacteristicOdor threshold:Not availablepH:Not applicable

Vapor pressure: $< 5 \text{ mm hg} (27 \, ^{\circ}\text{C} (80.6 \, ^{\circ}\text{F}))$ Boiling point/range: $> 149 \, ^{\circ}\text{C} (> 300.2 \, ^{\circ}\text{F})$ 

Melting point/ range:Not availableSpecific gravity:1.11

Vapor density:

Not available

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available

Not available

Slight

Not available

1.29 %; 12.34 g/l

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

vapours.

**Incompatible materials:** Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg (Estimated)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Bisphenol A fumarate resin	No	No	No
Cumene hydroperoxide	No	No	No

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate	Irritant, Allergen
Bisphenol A fumarate resin	Irritant, Allergen
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

## TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Not regulated Proper shipping name: Hazard class or division: None Identification number: None Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

### **United States Regulatory Information**

TSCA 12(b) Export Notification:

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory. None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA 313:

This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9). **CERCLA Reportable quantity:** Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.